

kopper[®]

KP-180-BP 2.4MP HD BULLET CAMERA



Key Features

- 180 degrees viewing angle
- 2.4mp high resolution
- Latest generation high quality chipset
- IK10 optional
- 1/2.7 HD CMOS Image sensor

FC CE RoHS

KP-180-BP

2.4MP HD BULLET CAMERA

Camera

| | |
|-------------------|--------------------------------------|
| Image Sensor: | 2.4MP 1 / 2.7 " HD CMOS Image Sensor |
| Signal System: | PAL/NTSC |
| Resolution: | 2.4mp |
| Shutter Time: | 1/25(1/30) s to 1/50,000 s |
| Lens Mount: | FISHEYE 1.7MM |
| Day& Night: | IR cut filter |
| Video Frame Rate: | 1080p@25fps/1080p@30fps |
| Synchronization: | Internal Synchronization |

Menu

| | |
|--------------|---|
| BLC: | Support |
| AGC: | Support |
| HLC: | Support |
| Digital WDR: | Yes |
| Language: | English |
| Function: | Brightness, Sharpness, Mirror, Smart IR |

Interface

| | |
|------------|---|
| Video Out: | Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P |
| Switch | OSD button to change modes |

General

| | |
|-----------------------|---|
| Operating Conditions: | -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing) |
| Power Supply: | 12 VDC±25% |
| IR Range: | Up to 30m |