

KP-HD24MP-B5 2.4MP HD 50MTRS BULLET



Key Features

- 1/2.7" HD CMOS sensor
- 2.4mp resolution
- 50 meters IR distance
- IP66 weatherproof housing



KP-HD24MP-B5

2.4MP HD 50MTRS BULLET

Image Sensor: 2.4MP 1 / 2.7 " HD CMOS Image Sensor Signal System: PAL/NTSC Resolution: 2.4mp Shutter Time: 1/25(1/30) s to 1/50,000 s Lens Mount: M12 6mm/ 8mm / 12mm (optional) Day& Night: IR cut filter Video Frame Rate: 1080p@25fps/1080p@30fps Synchronization: Internal Synchronization Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)	Camera	
Resolution: 2.4mp Shutter Time: 1/25(1/30) s to 1/50,000 s Lens Mount: M12 6mm/ 8mm / 12mm (optional) Day& Night: IR cut filter Video Frame Rate: 1080p@25fps/1080p@30fps Synchronization: Internal Synchronization Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Image Sensor:	2.4MP 1 / 2.7 " HD CMOS Image Sensor
Shutter Time: 1/25(1/30) s to 1/50,000 s Lens Mount: M12 6mm/ 8mm / 12mm (optional) Day& Night: IR cut filter Video Frame Rate: 1080p@25fps/1080p@30fps Synchronization: Internal Synchronization Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Signal System:	PAL/NTSC
Lens Mount: M12 6mm/ 8mm / 12mm (optional) Day& Night: IR cut filter Video Frame Rate: 1080p@25fps/1080p@30fps Synchronization: Internal Synchronization Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Resolution:	2.4mp
Day& Night: IR cut filter Video Frame Rate: 1080p@25fps/1080p@30fps Synchronization: Internal Synchronization Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Shutter Time:	1/25(1/30) s to 1/50,000 s
Video Frame Rate: 1080p@25fps/1080p@30fps Synchronization: Internal Synchronization Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Lens Mount:	M12 6mm/ 8mm / 12mm (optional)
Synchronization: Internal Synchronization Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Day& Night:	IR cut filter
Menu BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Video Frame Rate:	1080p@25fps/1080p@30fps
BLC: Support (optional) AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Synchronization:	Internal Synchronization
AGC: Support (optional) Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Menu	
Digital WDR: Yes Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	BLC:	Support (optional)
Language: English Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	AGC:	Support (optional)
Function: Brightness, Sharpness, Mirror, Smart IR Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Digital WDR:	Yes
Interface Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Language:	English
Video Out: Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Function:	Brightness, Sharpness, Mirror, Smart IR
Switch OSD button to change modes General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Interface	
General Operating -40 °C - 60 °C (-40 °F - 140 °F)	Video Out:	Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P
Operating -40 °C - 60 °C (-40 °F - 140 °F)	Switch	OSD button to change modes
	General	
Power Supply: 12 VDC±25%	Power Supply:	12 VDC±25%
IR Range: Up to 50m	IR Range:	Up to 50m

Disclamiar : Specifications & Designs subject to change without prior notice