

KP-HD24MP-DP/WL 2.4MP WARM LIGHT LED



Key Features

- With 2.4MP CMOS, Capture moving images
- Support AHD/TVI/CVI, excellent performance clear picture
- 0.01Lux@(F1.2,AGC ON), 0LUX with IR
- Support IR-CUT,CDS external control, D/N
- Support OSD/UTC
- Support DWDR
- Adaptive Digital Noise Reduction, 3D-DNR, 2D-DNR
- 6KV Lighting protection, with ECAP 220u
- Support DC 6-15V power
- 32x32 (mm)

KP-HD24MP-DP/WL

2.4MP WARM LIGHT LED DOME CAMERA

SPECIFICATION

Sensor:	1/2.9" CMOS HD Sensor
System:	PAL/NTSC
Effective Pixel:	1920(H) x 1080(V)
Illumination:	0.01Lux@ (F1.2,AGC ON), 0LUX with IR
Shutter:	AUTO
D/N:	EXT (Default) /AUTO/COLOR/B/W
Synchronously:	Internal
FPS:	1080P@25fps
Video output:	AHD/TVI/CVI/CVBS

OSD Menu

Exposure:	BRIGHTNESS / EXPOSURE MODE / GAIN
BW:	ATW/MWB
D/N:	EXT (Default) /AUTO/COLOR/B/W
Video Setting:	Contrast/Sharpness/COLOR GAIN/DNR/Format/DWDR
Language:	ENGLISH/CHN1/ESPAÑOL/FRANCAIS/CHN2/ Russian/ITALIANO/EAAHNIKA/POLSKI/Portuguese

Common

Operation Temperature:	-20° to 60°
Working Humidity:	Relative humidity less than 90%
Power:	DC12V(±20%) - 65mA
Size:	32*32/38*38 (mm)