

## KP-HD24MP-SLB 2.4MP STARLIGHT HD BULLET



### Key Features

- With 2.4MP CMOS, Capture moving images
- SONY IMX307 200W Starlight CMOS, capture images
- 4 in 1 signal with high definition output, clear image
- 0.01Lux@(F1.2,AGC ON), 0LUX with IR
- IR-CUT switch, CDS external control, D/N mode
- Support OSD menu, suitable for user-defined settings
- DWDR
- Auto adjusting 2D-DNR, 3D-DNR
- Support 6KV lightning protection, large power capacitor design

# KP-HD24MP-SLB

## 2.4MP STARLIGHT HD BULLET

### SPECIFICATION

Sensor:	1/2.8" Starlight Sony CMOS Sensor
Video Format:	PAL/NTSC
Effective Pixel:	1920(H) x 1080(V)
Illumination:	0.0001Lux@(F1.2, AGC ON), 0LUX with IR
Shutter:	AUTO
D/N:	External Control (Default) /Auto/Color/B&W
Synchronously:	inter-sync
FPS:	1080P@25fps
Signal:	AHD/TVI/CVI/CVBS (Optional)

### OSD Menu

Lens Mode:	Manual/DC Lens
Exposure:	Electronic Shutter/AGC/Frame /Brightness/DWDR/Fogging
Back-light Mode:	Close/Back-light Compensation/Strong Inhibition
W/B Mode:	Auto/AWE/Indoor/Outdoor/Manual /AWB
D/N Mode:	External Control (Default) /Auto/Color/B&W
DNR Type:	2DNR/3DNR
Video Setting:	Contrast/Sharpness/Saturation/DNR/Video Format/DWDR
Function:	Equipment Name/Digital/Motion Detection /Privacy Block/Language/Bad Point Compensation/RS485
Adjustment:	Sharpness/Display/Brightness/Compensation/NTSC/PAL
Exit:	Save and Exit/Reset/Non-save
Language:	Chinese1/Chinese2/German/French/Italian/Polish/Russian/Portuguese/ Dutch/Turkish/English

### Common

Working Temperature:	-20° to 60°
Working Humidity:	Relative humidity less than 90%
Power:	DC12V(±20%) - 50mA