

KP-HD2MP-B4X MINI HD PTZ Bullet Camera



Function Characteristic:

1. Adopt high performance 1/2.8" CMOS HD Sensor.
2. Using imported dot matrix large glass lamps and imported high-speed glass lamp light, to ensure the IR distance 60 m; product life can reach 30,000 hours.
3. Intelligent infrared control technology can automatically control the infrared light according to the environment. Under the premise of ensuring monitoring results, it can effectively enhance the infrared lamp's life and ensure the product stability.
4. Constant current circuit design, to ensure stable operation of the infrared light. And it won't reduce the infrared lamps' life which caused by the changing of the power supply.
5. Efficient cooling structure, using physical means heat, which can effectively reduce the temperature of the inside dome camera, to prevent the inner to be fogging, and to ensure the machine's stability.

KP-HD2MP-B4X

2MP MINI HD PTZ, 4X

Image Sensor:	1/2.8" CMOS HD Sensor
Horizontal resolution	1080P
Optical focus	4X
Min. Illumination:	0.01Lux @(F1.6,AGC ON), 0 Lux with IR
IR distance	60M
Video compression	H.264
Signal model	50HZ:25fps(1920 X 1080) 60HZ:30fps(1920 X 1080)
Lens :	2.8mm - 12mm
Lens Mount:	M12
Day and Night	ICR
Electronic shutter	1/25s ~ 1/100000s
DNR	2D/3D-DNR
Horizontal range	0°~260°
Vertical range	-5°~60°
Horizontal speed	0.5°~12°/ s
Vertical speed	0.5°~12°/ s
Presets	255
Cruise track	8 groups, each group for 16 presets
Patrol track	4 groups, each group record 3 mins
Protocol	PELCO-D/PELCO-P
Protection level	IP66
Bracket	Wall mounted
Dimension	153mm×93mm×130mm (L×W×H)
Weight	920g
Power	DC12V/2A
Work Temperature	-30°C~60°C