

## KP-IP2MP-36X 2MP IP PTZ Camera



### Function Characteristic:

1. Adopt high performance 1/2.7" CMOS (Starlight Sensor).
2. Support dual stream compression technology.
3. Using imported dot matrix large glass lamps and imported high-speed glass lamp light, to ensure the IR distance 150 m; product life can reach 30,000 hours.
4. Intelligent infrared control technology can automatically control the infrared light according to the environment. Under the premise of ensuring monitoring results, it can effectively enhance the infrared lamp's life and ensure the product stability.
5. Constant current circuit design, to ensure stable operation of the infrared light. And it won't reduce the infrared lamps' life which caused by the changing of the power supply.
6. Efficient cooling structure, using physical means heat, which can effectively reduce the temperature of the inside dome camera, to prevent the inner to be fogging, and to ensure the machine's stability.

# KP-IP2MP-36X

## 2MP IP PTZ Camera

Image sensor	1/2.7" CMOS (Starlight Sensor)
Horizontal resolution	1080P
Optical focus	36X
Focus length	2.8-12mm
Minimum illumination	0.01Lux @(F1.6, AGC ON), 0 Lux with IR
WIFI	support
Mobile App	camhi
IR distance	150 mtr
Video compression	H.264
Signal model	50HZ:25fps(1280 X 960) 60HZ:30fps(1280 X 960)
Video bit rate	32kbps-16Mbps
Day and Night	ICR
3D Control	Support
Electronic shutter	1/25s ~ 1/100000s
D-WDR	Support
DNR	2D/3D-DNR
Image direction	Mirror/ Flip
Privacy zone	Support
Mobile detection	Support
Horizontal range	0°~350°
Vertical range	0°~90°
Horizontal speed	0.5°~12°/ s
Vertical speed	0.5°~12°/ s
Presets	255
Cruise track	8 groups, each group for 16 presets
Patrol track	4 groups, each group record 3 mins
Network	RJ45
Rotation Speed	200° / s
Preset Pattern	255

Network protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
ONVIF	Support
Protection level	IP66
Bracket	Wall mounted
Weight	620g
Power	DC12V/5A
Work temperature	-30°C~60°C