

kopper[®]

KP-IP2MP-BM 2MP IP BULLET CAMERA



Key Features

- 1/2.8" Sony IMX sensor
- 1080p resolution
- H.265 compression
- Onvif support
- 30 meters IR distance
- IP66 weatherproof housing

FC CE RoHS

KP-IP2MP-BM

2MP IP BULLET CAMERA

Camera

Image Sensor:	1/2.8" Progressive Scan CMOS
Signal System:	PAL/NTSC
Min. Illumination:	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR 0.028 Lux @ (F2.0, AGC ON) ,0 Lux with IR
Shutter time:	1/3 s to 1/100,000 s
Lens:	3.6mm / 2.8mm
Lens Mount:	M12
Day& Night:	IR cut filter with auto switch
Wide Dynamic Range:	Digital WDR
Digital Noise Reduction:	3D DNR

Compression Standard

Video Compression:	H.264/ H.265
Video bit rate:	32Kbps~8Mbps
Audio Compression:	G.711/G.722.1/G.726/MP2L
Audio bit rate:	64Kbps(G.711) /16Kbps(G.722.1)/16Kbps(G.726) /32-128Kbps(MP2L2)
Dual Stream:	Yes

Image

Max. Image Resolution:	1920 x 1080
Frame Rate:	50Hz: 20fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 25fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Settings:	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
BLC:	Yes, zone configurable
3D DNR:	Support

Network

Protocols:	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, NTP,UPnP,SMTP,IGMP,802.1X,QoS,IPv6,Bonjour
General Function:	User Authentication, Watermark, IP address filtering, anonymous access, flickerless, heartbeat, video mask
System Compatibility:	ONVIF (Profile S, Profile G),ISAPI

KP-IP2MP-BM

2MP IP BULLET CAMERA

Interface

Audio:	Built In Audio (Optional)
Communication Interface:	1 RJ45 10M / 100M Ethernet interface

General

Operating Conditions:	-30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
Power Supply:	12 V DC \pm 10%, PoE (802.3at)
Power Consumption:	Max. 5.3W
Impact Protection:	IEC60068-2-75Eh, 50J; EN50102, IK10
IR Range:	Up to 30m
Protection Level:	IP66 rated