

kopper[®]

KP-IP5MP-DP 5MP IP DOME CAMERA



Key Features

- 1/2.8" Sony IMX sensor
- 2944 x 1656 resolution
- H.265 compression
- ONVIF support
- 30metres IR distance

FC CE RoHS

KP-IP5MP-DP

5MP IP DOME CAMERA 30mtrs

Camera	
Image Sensor:	1/2.8" Progressive Scan CMOS
Signal System:	PAL/NTSC
Min. Illumination:	Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR
Shutter Time:	1/3s to 1/100,000s
Slow shutter:	Support
Lens :	3.6mm
Lens Mount:	M12
Day& Night:	IR cut filter with auto switch
Digital WDR:	Yes
Digital noise reduction:	3D DNR
Focus:	Fixed

Compression Standard	
Video Compression:	H.264/H.265
Video bit rate:	32Kbps~16Mbps
Triple Streams:	Yes
Digital WDR:	Yes

Image	
Max. Image Resolution:	2944 × 1656
Frame Rate:	50Hz: 18 fps (2944 × 1656), 25 fps (2560 × 1440, 1920 × 1080, 1280 × 720) 60Hz: 20 fps (2944 × 1656), 30fps (2560 × 1440, 1920 × 1080, 1280 × 720)
Sub Stream:	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream:	50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement:	BLC/3D DNR/ROI
Image Settings:	Rotate mode, saturation, brightness, contrast, sharpness and white balance adjustable by client software or web browser

KP-IP5MP-DP

5MP IP DOME CAMERA 30mtrs

ROI: Support 1 fixed region for main stream and sub stream separately

Day/Night Switch: Day/Night/Auto/Schedule

Network

Network Storage: Local storage and NAS (NFS,SMB/CIFS), ANR

Protocols: TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6

General Function: Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering

System Compatibility: ONVIF (Profile S, Profile G), ISAPI

Interface

Communication Interface: 1 RJ45 10M / 100M Ethernet interface

General

Operating Conditions: -30 °C ~ 60 °C (-22 °F ~ 140 °F)
Humidity 95% or less (non-condensing)

Power Supply: 12 VDC \pm 25%, PoE (802.3af Class3)

Power Consumption: 12 VDC \pm 25%, 6W
PoE(802.3af, class 3), 7W

IR Range: Up to 30m