

## KP-XVR-08 8CH DVR



### Key Features

- 5mp Resolution
- H.265 plus compression
- Supports CVBS/ TVI/ AHD/ CVI & IP
- Hybrid (supports HD and IP both)
- iPhone & Android supported.



# KP-XVR-08

## 8CH DVR

### SYSTEM

Main processor: Hi3520DV400

### INTERFACE

Preview: 1/4/8/9

### VIDEO

Codec: H.265+

Monitor quality: VGA(1080P at most);HDMI (1080P at most)

Preview ability: 8\*5M-N@12fps (6 in 1) / 8\*4M-N @ 15fps (6in1)/  
8\*1080P@15fps (6in1) / 4\*1080P (6in1)

Encode ability: 8\*5M-N@6fps (6 in 1) / 8\*4M-N@8fps (6 in 1) /  
8\*1080P@8fps (6 in 1) / 4\*1080P@18fps (6 in 1)

Playback: 4\*5M-N@6fps (6 in 1) / 8\*4M-N@8fps (6 in 1) /  
8\*1080P@8fps (6 in 1) / 4\*1080P@18fps (6 in 1)

Multi-mode input: Analog: 8\*4M-N; 8\*1080N; 4\*1080P  
Digital to analog conversion: IP+HD  
Network: 16\*1080P; 8\*5M

Motion Detection: Each screen can be set to 192 (16\*12) detection areas; multi-level  
sensitivity can be set  
(Limited local channel)

### AUDIO

Audio compression: G.711A

Intercom: Support

### RECORD & PLAYBACK

Record mode: Manual>Alarm>Motion detection>Timing

Local Playback: 4ch (analog input mode)

Search mode: Search by time, calendar, event, channel

### STORAGE & BACKUP

Video storage: HDD, Network

Backup mode: Network, USB hard disk, USB burner, SATA burner

# KP-XVR-08

## 8CH DVR

### EXTERNAL INTERFACE

Video input:	8ch BNC
Video output:	1ch VGA, 1ch HDMI
Loop Vout	N/A
Network interface:	RJ45 10M/100Mself-adaption
PTZ control:	YES RS485 No (UTC Control)
USB:	2* USB 2.0ports
HDD:	2*SATA ports(Max 8TB/per)
Wireless:	3G, WIFI (extend via USB)

### GENERAL

Power supply:	12V/4A
Power Consumption:	<15W (without HDD)
Working environment:	Temperature: 0°C - +55°C, Humidity:10% - 90%, Atm:86kpa - 106kpa
Dimension:	254mm x 228.6mm
Weight:	1.052kg