

kopper[®]

KP-HD24MP-DP HD 2.4MP DOME 30MTRS



Key Features

- 1/2.7" HD CMOS sensor
- 2.4mp resolution
- TVI/CVI/AHD/CVBS selectable (optional)
- Upto 30 meters IR distance

FC CE RoHS

KP-HD24MP-DP

HD 2.4MP DOME 30MTRS

Camera

Image Sensor:	2.4MP 1 / 2.7 " HD CMOS Image Sensor
Signal System:	PAL/NTSC
Effective Pixels:	1920(H)*1080(V)
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens Mount:	M12 3.6mm / 2.8mm
Day& Night:	IR cut filter
Video Frame Rate:	1080p@25fps/1080p@30fps
Synchronization:	Internal Synchronization

Menu

BLC:	Support (optional)
AGC:	Support (optional)
Digital WDR:	Yes
Language:	English
Function:	Brightness, Sharpness, Mirror, Smart IR

Interface

Video Out:	Switchable TVI/AHD/CVI/CVBS @ 1080P / AHD/CVI/CVBS @ 720P
Switch	OSD button to change modes

General

Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±25%
IR Range:	Up to 30m