

**kopper**<sup>®</sup>

**KP-HD24MP-BVF550** 2.4MP VARIFOCAL BULLET



## Key Features

- 2.4 megapixel high performance CMOS
- Analog HD output, up to 1080p resolution
- Day/Night switch
- Smart IR
- Up to 50 meters IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

FC CE RoHS

# KP-HD24MP-BVF550

## 2.4MP VARIFOCAL BULLET

### Camera

Image Sensor	2.4MP CMOS image sensor
Signal System	PAL/NTSC
Effective Pixels	1920 (H) × 1080 (V)
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25 (1/30) s to 1/50,000 s
Lens	5mm to 50mm
Lens Mount	Φ14
Day & Night	ICR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
Synchronization	Internal synchronization
Video Frame Rate	25fps
HD Video Output	1 analog HD output
S/N Ratio	>62 dB

### General

Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity 90% or less (non-condensation)
Power Supply	12 VDC±15%
Power Consumption	Max. 4 W
Protection Level	IP66
IR Range	Up to 50 m